

# **Superior Detailed Maneuverability**

• Stable rotation from low to high speed reduces load shaking

### High Reliability


- Built-in large-capacity mechanical brake
- Long life

# **Lightweight and Compact**


- Integrated reducer
- Abundance of accessory functions (counterbalance valve, mechanical brake valve)

# WRD/CH Series









**WRD Series** 

#### [Main Application]

OWinch units for elevated work vehicles, mini crawler cranes, etc.

#### [Features]

- OLightweight and compact with its integrated drum structure
- OBuilt-in parking brake

[Main Application]

OWinch units for rough terrain cranes, truck cranes, etc.

### [Features]

- Orum-in type compact design
- OHigh-speed rotation support
- OBuilt-in parking brake
- O2-speed motor (high/low speed)



### Specification

		WRD010	CH05VA2	CH12VB2	CH18VB	CH04H	CH10VH
Rated Output Torque	N-m	1230	4600	11500	18000	3920	9810
Max. Output Speed	min-1	189	170	150	126	120	100
Max. Pressure	MPa	20.6	25	29.4	29.4	24.5	25
Rated Flow Rate (at counter balance valve)	L/min	70	155	280	400	155	155

#### Outline Dimensions

		WRD010	CH05VA2	CH12VB2	CH18VB	CH04H	CH10VH
А	mm	230	280	330	354	260	280
В	mm	166	210	270	290	200	210
С	mm	400	321	376	404	279	326
D	mm	75	241.3	280	324	200	265
E	mm	362.5	101	133	131	84.5	80
F	mm	441	341	453.5	482	341	332